Air Filter Mesh

BETAFENCE
INDUSTRY

Betafence NV
Deerlijkstraat 58A
B-8550 Zwevegem
Tel. +32 56 73 45 00
Fax +32 56 73 45 99
info@betafence.com
www.betafence.com

A range of different types of welded mesh in pregalvanized wire, stainless steel wire or galvanized after welding for delivery to the industrial user.

General use

Betafence is the worldwide leader for industrial applications with light and fine welded mesh. Betafence has an infinite range of mesh sizes, wire diameters and finishing possibilities so that you can find the optimal mesh for every application.
Fine and light welded mesh for filter applications can be made out of several wire diameters varying from 0,50 mm to 1,60 mm and is available in different mesh sizes.

Benefits

- A number of types available from stock
- Inherent strength
- No loose wires
- Quality assurance (EN ISO 9001:2000)
- A range of mesh configurations
- Minimum waste
- High quality based on more than 125 years of experience

Applications

Light welded mesh has countless uses for a number of applications such as screening, protection, support or reinforcement. Some examples are air filtration, ventilation & air conditioning.

Coatings

- Welded out of galvanized wire
- Galvanized after welding
- Welded out of stainless steel wire

Mesh width	Wire diameter	Width
6,35 x 6,35 mm	0,50 – 0,60 mm	max. 2000 mm
8 x 8 mm	0,50 – 0,80 mm	max. 2000 mm
10,6 x 10,6 mm	0,50 – 1,40 mm	max. 2000 mm
12,7 x 12,7 mm	0,50 – 1,60 mm	max. 2000 mm
16 x 16 mm	1,00 – 1,60 mm	max. 2000 mm
19 x 19 mm	1,00 – 1,60 mm	max. 2000 mm
25,4 x 12,7 mm	0,80 – 1,60 mm	max. 2000 mm
25,4 x 25,4 mm	0,80 – 1,60 mm	max. 2000 mm

Roll length: 25 / 50 / 100 / 150 m
Other mesh sizes and wire diameters on request